



# polygro



## Hailstop™ Netting & Accessories

POLYGRO PTY LTD | ABN. 42 088 164 863 | W. [www.polygro.com.au](http://www.polygro.com.au)


VICTORIA: A. 74 MCGREGORS DRIVE, KEILOR PARK VIC 3042 | T. (03) 9336 2132 | F. (03) 9336 2104

NEW SOUTH WALES: A. 5 FROST RD, CAMPBELLTOWN NSW 2560 | T. (02) 4628 8988 | F. (02) 4628 8922

QUEENSLAND: A. UNIT 1A 74-76 MAGNESIUM DRIVE, CRESTMEAD QLD 4132 | T. (07) 3278 5888 | F. (07) 3278 5855

## Hail Stop Quad Net

- Manufactured from (HDPE) high density polyethylene yarn
- The mesh aperture can be from 6mm to 16mm Hex or Diamond Pattern
- Colour: White, Black, Grey and Red
- Weight: 94 grams per m<sup>2</sup> (13mm Hex)
- Bale Size: Any width x 300m Length (minimum orders 1500kg)
- UV Treated - 10 Year pro-rata warranty against ultra violet damage
- Reinforced edge of 500mm on each side.
- Cloth marker tags on edges of the net along the full length of the net to denote 10 metre applied length
- Polygro Blue and Green marker yarns on one side of net



## Hail Stop Static Net

- Manufactured from (HDPE) high density polyethylene yarn
- The mesh is knitted with saw tooth pattern
- Colour: White
- Weight: 75 grams per m<sup>2</sup>
- Bale Size: 6.5m metres wide x 200 metres long
- UV Treated - 10 Year pro-rata warranty against ultra violet damage
- Reinforced eyelets 250mm and 750mm from edge so net can be used as 6.5m, 6.25m, 6m, 5.75m, 5.5m and 5m plus 100mm reinforced centre strip.
- Black cloth marker tags on edges of the net along the full length of the net to denote 10 metre applied length
- Polygro Blue and Green marker yarns on one side of net



## Hail Stop/Bird Stop Accessories

### 3.15mm Galvanized High Tensile Wire

- 3.15mm Outer Diameter
- Tensile Strength 1470 MPA
- Breaking Strain 1170kg
- Available in 1000 metre coil
- Weight per coil = 60kg



### 3.15mm Galvanized Splices

- 600mm length
- To be utilised on 3.15mm wire
- Powdered glass blend for extra grip on cable
- Tensile Strength 1320 MPA
- Available in 50 sets per carton




### 6mm High Tensile Galvanized Steel Cable

- 7 Strands x 2mm HT wire configuration
- 6mm Outer Diameter
- Tensile Strength 1570 MPA
- Breaking Strain 34.9 kn
- Available in 1000 metre reels (other lengths made to order)
- YB/T 5004-2001 Standards.
- ISO 9001:2000
- Weight per reel = 193kg



### 6mm & 7.5mm Galvanized Splices

- 1000mm length
- Powdered glass blend for extra grip on cable
- Both products to be utilised on 6mm or 7.5mm Cable
- Tensile Strength 1320 MPA
- Available in 50 sets per carton




### 7.5mm High Tensile Galvanized Steel Cable

- 7 Strands x 2.5mm HT wire configuration
- 7.5mm Outer Diameter
- Tensile Strength 1570 MPA
- Breaking Strain 51 kn
- Available in 1000 metre reels (other lengths made to order)
- YB/T 5004-2001 Standards.
- ISO 9001:2000
- Weight per reel = 300kg



### 6mm & 7.5mm PVC Netting Sleeves

- Manufactured with White K230 high impact rigid PVC Compound. This compound is also used for high impact marine applications.
- High UV performance
- Both products developed for application of sleeving netting over 6mm and 7.5mm diameter cable.
- Impact Strength (J/mm) 15.3
- Elongation at break 152%
- Each sleeve 40cm long x 250 sleeves per pack
- Omega profile



### Poly Link Netting Clips

- A & D logo Poly links by Polygro are manufactured using Du Pont 66 Base Nylon and conform to netting contractor standards when joining cable to nets.
- 250 Clips per pack, 20 x 250 packs per carton
- A & D logo Poly links by Polygro once closed are permanent and cannot be re-opened or reused.



**Other products available: Post Caps, Spare Net Bags, Repair Twines.**

**Consult Polygro Pty Ltd or a certified Engineer for site specific installation instructions.**